








HS Series 22 & 36 Starters &



Factory Installed Smart-R-Valve™!



HS starters are now available with a Smart-R-Valve[™] installed and tested at the factory. How easy is that?



All SAE ports are Straight Threaded O-ring Boss (ORB)

Hydraulic Starting Systems

Designed for the hydraulic fracturing market

Smart-R-Valve™...

The best hydraulic starting system in the "Fracking World"



SMART-R-VALVE

Say Goodbye to Pressure Spikes

Adjustments: None required Flow Rating: 50-80 GPM Temperature Range:

-40° to 180°

Consult factory for extreme ambient temperature applications.

PreEngages the pinion to ring gear
NO MORE broken ring gears
NO MORE broken drives
NO MORE broken nose cones
NO MORE downtime



Broken nose cone and drive on the first cycle.

Unbelievable Results!



The Smart-R-Valve™ Advantage

"We set up our test rig so we could break the starter drive and the nose cone of our test starter with just one cycle. With the addition of the Smart-R-Valve™ to the rig with the same pressures and flow we have gone thousands of cycles and the pinion and the drive looks like new."

- Ed Zaleski, Test Engineer


Services .


Hydraulic Starters


The **next generation hydraulic starter** with integrated **soft start** (smart R valve) in the back cover is available (released year: 2013)

For more information visit (https://powrquik.com/hydraulic-starters/)


- 1. HSV-223, HSV-224
- 2. HSCV-360







The higher the system pressure the more you need Smart-R-Valve™



POW-R-QUIK

ENGINE STARTING SYSTEMS

4540 West 160th Street, Cleveland, Ohio 44135 (216) 404 – 7112 sales@powrquik.com

